

## STANDARD GRADE APPLICATION TAPE








### BACKING

A standard weight latex saturated paper with high elongation, resistance to abrasion and moisture, with greater conformability to facilitate immediate placement and transfer of small to large graphics.

### ADHESIVE

A natural rubber adhesive with high tack levels to achieve more consistent transfer of computerized vinyl graphics regardless of size and type. The stable adhesive system permits longer time periods between application of the tape and the actual transfer.

### PHYSICAL SPECIFICATIONS

Adhesive		Natural rubber
Colour		White/Translucent
Tape Thickness (PSTC-33)		102 - 115 µm
*Adhesion to Steel (PSTC-1)		17 - 19 N/100 mm
Tensile (PSTC-31)		74 N/25 mm
Elongation		3 - 4 %
Tear Resistance		50 g

\* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.

### APPLICATIONS

- Application tape for small and medium sized vinyl graphics
- Clean transfer with wet application
- All purpose transfer and prespace tape

**WARRANTY:** R Tape warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user store the material in the original boxes (out of direct sunlight) from our factory. We also recommend that our material be stored at 21°C with 50% relative humidity. R Tape only warrants our products to be free from defects in workmanship or defects in R Tape material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.



**RESPONSIVE. RELIABLE. RESOURCEFUL.**