



**NESCHEN WALLPAPERS
AND WALLGRAPHICS**

 **GREEN WALL**


NESCHEN

WWW.NESCHEN.COM

NESCHEN WALLPAPERS AND WALLGRAPHICS



TYPICAL PROPERTIES

- PVC-free & solvent free manufacturing = green & odorless
- Up to 160 cm wide, minimum amount of joints = maximum design freedom and maximum print efficiency
- Range of textures
- Printing highlights the texture
- Customer specific textures available

INSTALLATION

- Virtually smooth back for better wall adhesion
- "Paste the wall" instead of "paste the paper"
- No shrinkage (unlike paper backed PVC wallpapers)

AFTER INSTALLATION

- Wash- and brushable like PVC wallpapers
- With latex and (eco) solvent: washable, required for the consumer market
- With UV: brushable, required for professional use (hotels, offices, etc.)
- Lightfastness: blue woolscale up to 5-6 (= 15-50 years indoor)
- Fire protection classification B/C-s1,d0 according to EN 13501 (printed and unprinted)

SUPPORT

- Formats for CE certification for printed finished wallpapers available to end customers

STATE-OF-THE-ART DIGITALLY PRINTABLE WALLPAPERS. MAKE YOU FEEL AT HOME.

Neschen **GREEN WALL** wallpapers are environmentally friendly and therefore the ideal LFP (large format printing) media for designing shopping malls, office buildings, exhibition booths, hotels, shops or private homes. They provide multiple possibilities for wall decoration and are easy to install and remove. Architects, designers and interior decorators have a wide selection available of individually configurable digitally printable wallpapers.



PRODUCT		TECHNICAL DATA				APPLICATIONS		INK-TECHNOLOGY					CERTIFICATES				
Category	Article	Thickness /Grammage	Texture	Width (cm)	Length (m)	Standard walls	PVC-free	Solvent	Latex	UV	LED UV	UVgel	B1	M1	EN 13501	ASTM E84	Certified for HP Latex Inks
	NESCHEN performance wallpaper smooth	190 g/m ²	smooth	106,7 160	50	•	•	•	•	•	•	•			•	•	•
	NESCHEN performance wallpaper classic	225 g/m ²	light textured	106,7 160	30	•	•	•	•	•	•	•			•	•	•
	NESCHEN wallpaper LITE smooth	190 g/m ²	smooth	160	50	•	•	•	•	•	•	•			•	•	•
	NESCHEN wallpaper LITE sand	215 g/m ²	sand	160	50	•	•	•	•	•	•	•			•	•	•
	NESCHEN wallpaper L-UV smooth FR	170 g/m ²	smooth	160	50	•	•		•	•	•	•			•	•	•
	NESCHEN wallpaper L-UV sand	175 g/m ²	sand	160	50	•	•		•	•	•	•		•	•	•	•
WALLGRAPHIC high-tack adhesive	NESCHEN PP wall-grip L-UV smooth	90 µm	smooth	137,2 160	50	•	•		•	•	•	•	•				•
	NESCHEN PP wall-grip L-UV sand	120 µm	sand	160	50	•	•		•	•	•	•	•				•
	solvoprint® performance wall-grip	100 µm	smooth	137,2 155	50	•		•	•	•	•	•	•		•		•

NESCHEN COATING GMBH

Hans-Neschen-Str. 1
31675 Bückeburg, Germany

T +49 (0)5722 2070

F +49 (0)5722 207 197

E info@neschen.de

www.neschen.com



WWW.NESCHEN.COM