

## Specifications Cordstrap CornerLash® AAR 200LE.4 20 FT

Performance Specifications	
Solution Breaking Strength*	24.000 daN / 52.800 lbf (±10%)
Solution MSL	12.000 daN / 26.400 lbf (±10%)
Certification	AAR & DNV-GL witnessed, Mariterm, Eurosafe

Specifications Cordstrap CornerLash AAR 200LE.4 20 FT	
<b>Construction &amp; Dimensions</b>	Four Horizontal pieces of woven lashing joined by 4 buckles. Each part of lashing is looped through Corner element* included in the Corner post**. Dedicated to 20-foot containers operated by railway under the authority of Association of American Railroads. * Corner element – patented external anchor point ** Corner post - ISO standardized load-carrying element, part of the steel framework of box container
<b>Designed for</b>	Rigid packaging, Soft packaging, Drums, IBC's, FIBC's (big bags)
<b>Lashing</b>	
- Length	15 m / 49.2' (±2%) – 4 pieces
- Width	40 mm / 1.57" (±5%)
- Elasticity	≤ 4%
- Color	orange
<b>Dynamic load buckle</b>	
- Width	40 mm / 1.57" (±5%)
<b>Corner element</b>	4 pieces
<b>Corner element spring</b>	4 pieces
<b>Packaging</b>	
Pieces per Box	1
Boxes on pallet	64
Box Weight	13.36 kg / 29.46 lbs
Box Dimensions	285 x 186 x 200 mm
Item number	7256558
<b>Material</b>	
Lashing	High tenacity polyester filament yarn
Corner element	Galvanized steel
Corner element spring	Galvanized steel
Buckle	Silver zinc coated dropforged steel buckle
Packaging	The solution is packed in corrugated fiberboard (recycling code 20)



Represented in over 50 countries

World market leader

ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance

Recommended Tensioner(s)	
<b>Battery Tensioner CBT 40</b> Product Code all regions type 7583000 <b>Battery Tensioner CBT 50</b> Product Code all regions type 7583000	<b>Pneumatic Tensioner CT 40 PN</b> Product code 7567000 <b>Pneumatic Tensioner CT 50 PN</b> Product code 7565000

Recommended Accessories	
<b>Container Magnets</b> Packaging 2 pieces per box  Product Code 7555000	<b>Cargo protection</b> See more information in Add-Ons Commercial spec. sheet to find products for supporting your application

Links to instruction sheet						
						
Steel drums	Plastic drums	IBC's	Soft packaging	Small big bags	High big bags	Crates/boxes
						

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F.  
 All information provided is based on accuracy at time of creation.



Represented in over 50 countries

World market leader

ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance